PRELIMINARY AMENDMENT
Title: DEVICE AND SYSTEM FOR RECORDING THE MOTION OF A WAFER AND METHOD
THEREFORE
Attorney Docket No. 135.009US01

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of claims:

1. (Original) A system for detecting, identifying, and locating any mechanical malfunction, which has caused, or could cause, defects in a wafer manufactured by semiconductor process and inspection machines in the course of the actual manufacturing process or in test cycles of said machines, said system comprising:

   - a test wafer, comprising a miniature electronic recording system, which comprises at least one accelerometer and circuitry for recording data that characterizes the motion of said test wafer, including fine perturbations and vibrations in its motion during its progress through and between said semiconductor process and inspection machines;

   - a computer, comprising: software for initializing and downloading recorder programs to said miniature electronic recording system before said test wafer is placed in said semiconductor process and inspection machines; software for transferring said data that characterizes the motion of said test wafer from said miniature electronic recording system to said computer; known data, which describes the "known good" behavior of a wafer during its progress through and between said semiconductor process and inspection machines; and software for detecting, identifying, and locating said mechanical malfunction; and

   - a reader station, comprising an AC power supply, interface circuits between said test wafer and said computer, and, if necessary, a battery charger;

   wherein;

   - said recorder programs cause said data that characterizes the motion of said test wafer to be recorded along the entire path of said test wafer through and between said semiconductor process and inspection machines; and

PRELIMINARY AMENDMENT
Title: DEVICE AND SYSTEM FOR RECORDING THE MOTION OF A WAFER AND METHOD THEREFORE
Attorney Docket No. 135.009US01

Page 4 of 10

- said software for detecting, identifying, and locating said mechanical malfunction detects, identifies, and locates said mechanical malfunction by comparing said recorded data that characterizes the motion of said test wafer with said known data.

2. (Currently Amended) The A system according to claim 1, wherein the test wafer is selected from the group comprising:
   - wafers whose surface area and, shape, thickness, and weight are essentially equal to those of standard size production wafers; and
   - wafers whose surface area and shape are essentially equal to those of standard size production wafers but whose thickness and/or weight differ from those of standard size production wafers.

3. (Currently Amended) The A system according to claim 2, wherein the test wafer is made from a material selected from the group comprising:
   - silicon;
   - aluminum;
   - glass;
   - gallium arsenide;
   - ceramic material; and
   - plastic.

4. (Currently Amended) The A system according to claim 1, wherein the miniature electronic recording system is attached to the test wafer by means selected from the group comprised of:
   - gluing;
   - screwing; and
   - bolting.bolting;

5. (Currently Amended) The A system according to claim 1, wherein the

PRELIMINARY AMENDMENT
Title: DEVICE AND SYSTEM FOR RECORDING THE MOTION OF A WAFER AND METHOD
THEREFORE
Attorney Docket No. 135.009US01

Page 5 of 10

components of the miniature electronic recording system are mounted on one or more circuit boards.

6. (Currently Amended) The A system according to claim 1, wherein the miniature electronic recording system is covered by an epoxy block molded on the wafer.

7. (Currently Amended) The A system according to claim 1, wherein a thin hermetic external cover is mounted over the miniature electronic recording system and is attached to the wafer.

8. (Currently Amended) The A system according to claim 7, wherein the hermetic thin casing has a thickness such that the maximum height of the electronics and cover is preferably no more than 2mm.

9. (Currently Amended) The A system according to claim 7, wherein the hermetic thin casing is made of a material chosen from the group comprised of:
    - aluminum;
    - stainless steel;
    - composite materials;
    - polyurethane;
    - silicon;
    - ceramic materials; and
    - plastic.

10. (Currently Amended) The A system according to claim 1, wherein the miniature electronic recording system additionally comprises components selected from the group comprised of:
    - analog-to-digital converters;
    - microprocessors;
    - batteries;

PRELIMINARY AMENDMENT
Title: DEVICE AND SYSTEM FOR RECORDING THE MOTION OF A WAFER AND METHOD
THEREFORE
Attorney Docket No. 135.009US01

Page 6 of 10

- memory units;

- temperature sensors;

- analog multiplexers;

- analog filters;

- peak-detectors; and

- sample-and-hold electronic circuits.

11. (Currently Amended) The A system according to claim 1, wherein the accelerometers are

selected from the group comprised of:

- dual-axis accelerometers;

- 3-axis accelerometers; and

- piezoelectric accelerometers.

12. (Currently Amended) The A system according to claim 10, wherein the analog-to-digital

converter includes an analog multiplexer, which enables the digitizing of a multitude of

analog signals.

13. (Currently Amended) The A system according to claim 10, wherein the microprocessor

includes a real-time clock and internal program memory.

14. (Currently Amended) The A system according to claim 10, wherein the battery is a

rechargeable battery.

15. (Currently Amended) The A system according to claim 14, wherein the rechargeable

battery is a lithium polymer battery.

16. (Currently Amended) The A system according to claim 10, wherein the memory unit is

composed of RAM memory and/or Flash memory.

17. (Currently Amended) The A system according to claim 1, wherein additional sensors are

PRELIMINARY AMENDMENT
Title: DEVICE AND SYSTEM FOR RECORDING THE MOTION OF A WAFER AND METHOD
THEREFORE
Attorney Docket No. 135.009US01

Page 7 of 10

attached to the test wafer, said sensors being suitable to measure parameters selected from

the group comprised of:

- temperature;

- light;

- pressure;

- air-flow;

- gas flow;

- humidity;

- clearance;

- electric field; and

- magnetic field.

18. (Currently Amended) The A system according to claim 1, wherein a miniature

camera is attached to the test wafer.

19. (Currently Amended) The A system according to claim 1, wherein the miniature

electronic recording system detects the motion of the test wafer to which it is

attached and uses the presence or absence of said motion to switch off or wake up

said electronics in order to conserve power.

20. (Currently Amended) The A system according to claim 1, wherein the interface

circuits of the reader station are electronic interface circuits.

21. (Currently Amended) The A system according to claim 1, wherein the interface

circuits of the reader station are non-contact interface circuits.

22. (Currently Amended) The A system according to claim 21, wherein the non-

contact interface circuits of the reader station are optical interface circuits or radio

frequency interface circuits.

PRELIMINARY AMENDMENT
Title: DEVICE AND SYSTEM FOR RECORDING THE MOTION OF A WAFER AND METHOD THEREFORE
Attorney Docket No. 135.009US01

Page 8 of 10

23. A method for using a record of the motion of a test wafer, including fine perturbations and vibrations in the motion of said wafer, during its progress through and between semiconductor process and inspection machines in the course of the actual manufacturing process or in test cycles of said machines, to detect, identify, and locate any mechanical malfunction of the processing machine which has caused, or could cause, defects in the manufactured wafer, comprising the following steps:

- placing said test wafer on the reader station;
- initializing said test wafer;
- transferring said test wafer to said processing machine;
- operating said processing machine under normal operating conditions;
- recording, in the miniature electronic recording system mounted on said test wafer, data from at least one accelerometer, said data characterizing the motion of said test wafer;
- processing the signals from the accelerometer on said test wafer;
- returning said test wafer to said reader station;
- ownloading said recorded data into a computer;
- erasing, if desired, said data recorded in said of said miniature electronic recording system; and
- etecting, identifying, and locating any mechanical malfunction of the processing machine;

wherein;

- said data that characterizes the motion of said test wafer is recorded along the entire path of said test wafer through and between said semiconductor process and inspection machines; and
- the software of said computer detects, identifies, and locates said mechanical malfunction by comparing said recorded data characterizing the motion of said test wafer with known data previously stored in the memory of said computer.

PRELIMINARY AMENDMENT
Title: DEVICE AND SYSTEM FOR RECORDING THE MOTION OF A WAFER AND METHOD
THEREFORE
Attorney Docket No. 135.009US01

Page 9 of 10

24. (Currently Amended) The A method according to claim 23, wherein initializing

the test wafer includes some or all of the following steps:

- recharging a battery on said test wafer;

- downloading different versions of recording programs and/or other

  parameters from the computer into the memory of said test wafer; and

- initializing the real-time clock on said test wafer.

25. (Currently Amended) The A method according to claim 23, wherein the signals

are processed using one of the strategies selected from the group comprising:

- on-wafer signal processing followed by low sampling-rate signal digitizing; and

- high-rate signal sampling followed by computer-based signal processing.

26. (Currently Amended) The A method according to claim 23, wherein the known

data to which the recorded data is compared is selected from the group

comprising:

- the precise known time-schedule of events inside the processing machine; and

- "known-good" readings or "fingerprints" of signals previously recorded on the

  same or on similar processing machine.

27. (Currently Amended) The A method according to claim 23, wherein comparing the

recorded data to known data additionally comprises the use of special software for signal

recognition to automatically detect and interpret "known" problems.